

## Single doors

Timber	Sapele
	Accoya
Frame depth	83
	92
	105
Projection cill option	25
	50
	75
Door thickness	48
	57
	70
Glazing rebate depth	14
Glazing method	Internal timber bead
Glass options	4 / 8 / 4
	6.4 / 6 / 4
	4 / 12 / 4
	6.4 / 10 / 4
	4 / 16 / 4
	6.4 / 14 / 4
	12
	14
	20
	12 / 8 / 4
	12 / 6 / 6.4
	14 / 6 / 4
	4 / 14 / 4 / 12 / 4
	6.4 / 12 / 4 / 12 / 4
	20 / 10 / 6.4
	20 / 12 / 6.4
	20 / 14 / 4
	40
	Glazing bar options
22mm SDL - Bevel (EXT) Lambs tongue (INT)	
22mm TDL - Bevel (EXT) Lambs tongue (INT)	
33mm TDL - Bevel (EXT) Lambs tongue (INT)	
Hinge type	Butt hinge
Locking mechanism	Multipoint lock
Threshold material	Timber
	Extruded aluminium
Panel options	Solid timber
	Insulated timber
	Timber with steel reinforcement
Security rating	T.B.C.
Acoustic rating	T.B.C.
Weather ratings	T.B.C.
U-value rating	T.B.C.
Energy rating	T.B.C.
Paint	40 Colours - Multi-coat, spray applied factory finished system
Hardware	Standard - T.B.C. finishes
	Premium - T.B.C. finishes

## Double doors

Timber	Sapele
	Accoya
Frame depth	83
	92
	105
Projection cill option	25
	50
	75
Door thickness	48
	57
	70
Glazing rebate depth	14
Glazing method	Internal timber bead
Glass options	4 / 8 / 4
	6.4 / 6 / 4
	4 / 12 / 4
	6.4 / 10 / 4
	4 / 16 / 4
	6.4 / 14 / 4
	12
	14
	20
	12 / 8 / 4
	12 / 6 / 6.4
	14 / 6 / 4
	4 / 14 / 4 / 12 / 4
	6.4 / 12 / 4 / 12 / 4
	20 / 10 / 6.4
	20 / 12 / 6.4
	20 / 14 / 4
	40
Glazing bar options	17mm SDL - Bevel (EXT) Lambs tongue (INT)
	22mm SDL - Bevel (EXT) Lambs tongue (INT)
	22mm TDL - Bevel (EXT) Lambs tongue (INT)
	33mm TDL - Bevel (EXT) Lambs tongue (INT)
Hinge type	Butt hinge
Locking mechanism	Multipoint lock
Threshold material	Timber
	Extruded aluminium
Panel options	Solid timber
	Insulated timber
	Timber with steel reinforcement
Security rating	T.B.C.
Acoustic rating	T.B.C.
Weather ratings	T.B.C.
U-value rating	T.B.C.
Energy rating	T.B.C.
Paint	40 Colours - Multi-coat, spray applied factory finished system
Hardware	Standard - T.B.C. finishes
	Premium - T.B.C. finishes

## French/Balcony doors

Timber	Sapele
	Accoya
Frame depth	83
	92
	105
Projection cill option	25
	50
	75
Door thickness	48
	57
	70
Glazing rebate depth	14
Glazing method	Internal timber bead
Glass options	4 / 8 / 4
	6.4 / 6 / 4
	4 / 12 / 4
	6.4 / 10 / 4
	4 / 16 / 4
	6.4 / 14 / 4
	12
	14
	20
	12 / 8 / 4
	12 / 6 / 6.4
	14 / 6 / 4
	4 / 14 / 4 / 12 / 4
	6.4 / 12 / 4 / 12 / 4
	20 / 10 / 6.4
	20 / 12 / 6.4
	20 / 14 / 4
	40
	Glazing bar options
22mm SDL - Bevel (EXT) Lambs tongue (INT)	
22mm TDL - Bevel (EXT) Lambs tongue (INT)	
33mm TDL - Bevel (EXT) Lambs tongue (INT)	
Hinge type	Butt hinge
Locking mechanism	Multipoint lock
Threshold material	Timber
	Extruded aluminium
Panel options	Solid timber
	Insulated timber
	Timber with steel reinforcement
Security rating	T.B.C.
Acoustic rating	T.B.C.
Weather ratings	T.B.C.
U-value rating	T.B.C.
Energy rating	T.B.C.
Paint	40 Colours - Multi-coat, spray applied factory finished system
Hardware	Standard - T.B.C. finishes
	Premium - T.B.C. finishes

## Folding doors

Timber	Sapele
	Accoya
Frame depth	150
Projection cill option	25
	50
	75
Door thickness	57
Glazing rebate depth	14
Glazing method	Internal timber bead
Glass options	4 / 8 / 4
	6.4 / 6 / 4
	4 / 12 / 4
	6.4 / 10 / 4
	4 / 16 / 4
	6.4 / 14 / 4
	12
	14
	20
	12 / 8 / 4
	12 / 6 / 6.4
	14 / 6 / 4
	Glazing bar options
22mm SDL - Bevel (EXT) Lambs tongue (INT)	
22mm TDL - Bevel (EXT) Lambs tongue (INT)	
33mm TDL - Bevel (EXT) Lambs tongue (INT)	
Hinge type	Folding hardware
Locking mechanism	Multipoint lock
	Drop bolts
Threshold material	Timber
	Extruded aluminium
Panel options	Solid timber
	Insulated timber
	Timber with steel reinforcement
Security rating	T.B.C.
Acoustic rating	T.B.C.
Weather ratings	T.B.C.
U-value rating	T.B.C.
Energy rating	T.B.C.
Paint	40 Colours - Multi-coat, spray applied factory finished system
Hardware	Standard - T.B.C. finishes
	Premium - T.B.C. finishes

## Lift & Slide doors

Timber	Sapele
	Accoya
Frame depth	**Varies depending on door configuration**
Projection cill option	25
	50
	75
Door thickness	57
Glazing rebate depth	14
Glazing method	Internal timber bead
Glass options	4 / 8 / 4
	6.4 / 6 / 4
	4 / 12 / 4
	6.4 / 10 / 4
	4 / 16 / 4
	6.4 / 14 / 4
	12
	14
	20
	12 / 8 / 4
	12 / 6 / 6.4
	14 / 6 / 4
	Glazing bar options
22mm SDL - Bevel (EXT) Lambs tongue (INT)	
22mm TDL - Bevel (EXT) Lambs tongue (INT)	
33mm TDL - Bevel (EXT) Lambs tongue (INT)	
Hinge type	Lift & Slide hardware
Locking mechanism	Multipoint lock
Threshold material	Timber
	Extruded aluminium
Panel options	Solid timber
	Insulated timber
	Timber with steel reinforcement
Security rating	T.B.C.
Acoustic rating	T.B.C.
Weather ratings	T.B.C.
U-value rating	T.B.C.
Energy rating	T.B.C.
Paint	40 Colours - Multi-coat, spray applied factory finished system
Hardware	Standard - T.B.C. finishes
	Premium - T.B.C. finishes